

TransTac Plus Curtains without folded edges

TransTac Plus curtains are used for exceptional performance especially

- for grinding
- when strength and durability of the PVC is required
- when conventional curtains are easily damaged
- when the coverage of strips are not sufficient
- for closed cabins
- for isolation



TransTac Plus-curtains in T40 (red-orange)

Possible sizes and dimensions:

- Standard width 1500 mm
- Special widths: standard width < 1500 mm on demand
- Maximum height: approx. 5 m
- Thickness: 2,0 mm

TransTac Plus curtains T75 are only available with smooth surface

TransTac Plus Curtains, 2mm thick, 1500 wide – without folded edges

Protective curtains for exceptional performance: With 8 reinforced eyelets (approx. 200 mm distance apart) along the top, with snap fasteners down each side to join more than one curtain together, 2.0 mm thick. Curtains are made to order.

Curtain model:	T75	T55	T50	T40	T0		
	dark green	eurogreen	red-brown	red-orange	clear		
Certificates: SINO DIN EN 1598 1S151						Resistance to ignition according to DIN EN 1598. Unsuitable for arc welding.	
Risk factor	approx. 0,05	approx. 0,40	approx. 0,70	approx. 0,80	–		
Size	Weight	Article no.	Article no.	Article no.	Article no.	Article no.	Price €/pc.
1.600 mm	6,0 kg/pc.	TTP-T75-2MM-160	TTP-T55-2MM-160	TTP-T50-2MM-160	TTP-T40-2MM-160	TTP-T0-2MM-160	121,30/pc
1.800 mm	6,75 kg/pc.	TTP-T75-2MM-180	TTP-T55-2MM-180	TTP-T50-2MM-180	TTP-T40-2MM-180	TTP-T0-2MM-180	135,80/pc
2.000 mm	7,2 kg/pc.	TTP-T75-2MM-200	TTP-T55-2MM-200	TTP-T50-2MM-200	TTP-T40-2MM-200	TTP-T0-2MM-200	150,20/pc
Special length*	2,5 kg/m ²	TTP-T75-2MM-SL	TTP-T55-2MM-SL	TTP-T50-2MM-SL	TTP-T40-2MM-SL	TTP-T0-2MM-SL	52,00/m ²
Special width*	2,5 kg/m ²	TTP-T75-2MM-SG	TTP-T55-2MM-SG	TTP-T50-2MM-SG	TTP-T40-2MM-SG	TTP-T0-2MM-SG	64,70/m ²

Delivery time approx. 2 weeks

* Minimum price for custom made curtains is 50 €/pc.